

The Effect of Ultra Large Container Vessels on Cranes and Infrastructure

Port and Terminal Technology Conference
April 2017, Norfolk, Virginia

Erik Soderberg, SE
Structural Engineer, President
Liftech Consultants Inc.
www.Liftech.net



Liftech

Overview

Section 1: Vessel Changes

Section 2: STS Crane Requirements

Section 3: Infrastructure Requirements



Section 1: Vessel Changes


Liftech

Ultra Large Container Vessels



CMA CGM Benjamin Franklin at Port of Long Beach

Ship Size Growth






Section 2: STS Crane Requirements

Liftech


ULCV Crane Requirements



Notes:

1. Outreach based on 1 degree list and 1 m trolley overrun.
2. Lift dimensions depend on operations; amounts shown are approximate. Dimensions shown are based on: 8.5' tall top box with 1' clear, 1 degree list, and 12.5 m of draft.

Crane Raising on the US West Coast



Typical crane raise: 7 m to 10.5 m

New lift height: 44.5 m to 46.5 m

Crane Raise with Jacking Frames



Crane Modifications - Some Considerations

1. Design ship
2. Stability, ballast, and wheel loading/girder capacity
3. Construction impact to terminal operations
4. Electrical system upgrade?
5. Seismic upgrade?
6. Main hoist drum - rope capacity
7. Boom hoist lift capacity
8. Other – see speaker notes



Cost to Modify Existing Cranes

Cost can vary significantly depending on:

- Scope of structural modifications


- Location and local labor

- Scope of mechanical and electrical modifications such as rope drums, trolley cable reel, machinery house service cranes, cabling, lighting, access ways, new wire rope, etc.

Estimated cost per crane for short raise with low labor cost – around US\$1.5M

Estimated cost per crane for tall raise with boom extension and high labor cost - US\$4-5M

Section 3: Infrastructure



Liftech

Berth Space

ULCV lengths are not much longer than the previous generation.

Some berths require additional length – a costly option.

Less costly – install more compact crane stops closer to wharf end, add a mooring dolphin beyond the wharf (*see next slide*).



Mooring Dolphin

Add a mooring dolphin beyond wharf so the vessel can be located closer to the end of the wharf.



Mooring Dolphin at IMTT Port of Richmond

Berthing Fenders

UCLV berthing velocities and angles are typically much less than those in traditional design guidelines.



Consider recent data when determining berthing energies.

A cost-benefit analysis may justify the acceptance of existing systems.

Bollards

Increased mooring forces may require higher-capacity bollards. Installing higher-capacity bollards requires relatively little cost unless the wharf structure needs strengthening.


Consider site-specific wind speeds and directions when determining required bollard capacities.



Arrangement and Bitt Loading



www.bigstock.com · 165277886



www.alamy.com - BT1B6K



Wheel Loads

Wheel loads may exceed the design or rated capacity of existing wharf girders.

Options to address excessive crane loads include:

- Optimize crane design



- Analyze or load test structure & foundation (*see next slide*)

- Strengthen existing girders

- Replace girder systems with new, stronger systems

- Increase crane rail gage for new cranes

Justify Increased Rated Girder Capacity – Girder Strength




Justify Increased Rated Girder Capacity – Piling Capacity


Analyze pile driving records

Pile dynamic analysis through testing

Load test




PILE LOAD TEST ARRANGEMENT



PILE LOAD TEST DETAIL

Crane Girder Strengthening



Summary

ULCVs affect STS cranes and wharf infrastructure.

STS cranes outreach 23 containers wide, 58 m from fender face.

STS lift height above high water about 50 m.

Increased vessel lengths are limited but may be significant.


Consider low cost modifications such as new and relocated crane stops, mooring dolphins beyond wharf.

Fenders for smaller 12,000 TEU range vessels may be adequate.

Increased mooring forces may require larger bollards. Costs are limited unless wharf strengthening is required.

Consider performing a crane girder study to justify additional capacity before strengthening or replacing.

Consider performing a study to determine your terminal requirements and the most cost effective approaches.



Variables – for estimating outreach and lift height

- a Average container spacing, typically 2.5 m
- b Average container width, typically 2.44 m (8' 0")
- CH Container height of top container, typically 2.59 m (8' 6")
- CL Clearance between top of top container and lifted container
- D Draft, see Approximations Note
- DWL Design water level elevation
- h Height from fender centerline to top of top container
- H Height from keel to top of containers without list
- Lift Lift height above top of rail (TOR) = $H + CL + CH + (N_H/2) \times a \times \sin \theta - DD - RH$
- List_H Horizontal movement of top container due to ship list, approximately $h \times \tan \theta$
- List_V Vertical movement of outermost top container due to ship list, approximately $(N_H/2) \times a \times \sin \theta$
- N_H Number of containers horizontally across deck
- N_V Number of containers stacked vertically in hull and on deck
- OR Outreach
- OV Overrun: additional distance to avoid trolley slowdown
- RH Distance from TOR to DWL
- SB Setback, the typical range is from 2 m to 6 m
- θ Ship list design angle, degrees
- TOR Top of waterside gantry rail

Approximate Outreach

| | SB, m | 2.0 | 4.0 | 6.0 |
|----------------|----------------|------|-------------|------|
| | θ , deg | 1.0 | 1.0 | 1.0 |
| | OV, m | 1.0 | 1.0 | 1.0 |
| N _H | a x n, m | h, m | Outreach, m | |
| 13 | 32.5 | 30.0 | 34.8 | 36.8 |
| 14 | 35.0 | 32.9 | 37.4 | 39.4 |
| 15 | 37.5 | 32.9 | 39.9 | 41.9 |
| 16 | 40.0 | 32.9 | 42.4 | 44.4 |
| 17 | 42.5 | 35.8 | 44.9 | 46.9 |
| 18 | 45.0 | 35.8 | 47.4 | 49.4 |
| 19 | 47.5 | 38.7 | 50.0 | 52.0 |
| 20 | 50.0 | 38.7 | 52.5 | 54.5 |
| 21 | 52.5 | 38.7 | 55.0 | 57.0 |
| 22 | 55.0 | 38.7 | 57.5 | 59.5 |
| 23 | 57.5 | 38.7 | 60.0 | 62.0 |
| 24 | 60.0 | 41.6 | 62.5 | 64.5 |
| 25 | 62.5 | 41.6 | 65.0 | 67.0 |
| 26 | 65.0 | 41.6 | 67.5 | 69.5 |

Approximate Lift Height

| | RH, m | 2.0 | 3.0 | 4.0 |
|----------------|----------------|------|--------------------|------|
| | θ , deg | 1.0 | 1.0 | 1.0 |
| | CL, m | 0.5 | 0.5 | 0.5 |
| N _V | H, m | D, m | LH, Lift Height, m | |
| 14 | 41.4 | 10.7 | 32.1 | 31.1 |
| 15 | 44.1 | 11.0 | 34.5 | 33.5 |
| 16 | 46.9 | 11.4 | 36.9 | 35.9 |
| 17 | 49.6 | 11.8 | 39.3 | 38.3 |
| 18 | 52.4 | 12.1 | 41.7 | 40.7 |
| 19 | 55.1 | 12.5 | 44.1 | 43.1 |
| 20 | 57.9 | 12.9 | 46.5 | 45.5 |
| 21 | 60.6 | 13.2 | 48.9 | 47.9 |
| 22 | 63.4 | 13.6 | 51.3 | 50.3 |

Approximations Note

Approximate values are provided for general understanding. Variables used are estimates based on a variety of projects. Actual values will vary for a particular location, ship, crane, and operation.

Disclaimer: This guide has been prepared in accordance with recognized engineering principles and is intended for use only by competent persons who, by education, experience, and expert knowledge, are qualified to understand the limitations of the guide. The publication of the information is not intended as a representation or warranty by Liftech Consultants Inc. Liftech Consultants Inc. does not guarantee that the guide is error free.

Anyone making use of the information assumes all liability arising from such use.

Copyright ©2013 by Liftech Consultants Inc. A California Corporation. All rights reserved.